



Industrial Grade Rough Terrain Scissor Lifts

Models
2591 RT
3391 RT
4191 RT

- Fully proportional drive and lift controls
- No-maintenance scissor bearings
- Roll-out deck extensions with incremental locking positions
- Non-skid steel deck construction
- Large sheet loading entrance
- Easy maintenance access without raising platform or swing-out trays
- Quad-Trax™ 4wd power package
- Outrigger support for platform stability on heavy duty jobs sites with “one-touch” auto leveling
- Powered by liquid-cooled engine
- Multiple fuel selections (gasoline/liquid propane or diesel)
- Oscillating rear axle with 12” (30.48 cm) ground clearance



Features

Work Area

Roll-out deck extension with incremental locking positions
Large sheet loading entrance accommodates 48" (1.22 m) material

110V Power to Platform

Combination of wide beams and large pins in self-lubricating bearings for larger load bearing surface in scissor pivot areas

Performance

Fully proportional drive and lift controls

Oscillating rear axle with 12" (30.48 cm) ground clearance

Quad-Trax™ 4wd Power Package

Engine/Power

Multiple Fuel Selections (gasoline/liquid propane or diesel)

Liquid-Cooled Engine

Serviceability

Lubrication-Free Scissor Bearings

Easy maintenance access to mechanical and electrical components without raising platform or swinging out trays

Logically grouped components and numbered wiring for easy reference

Safety

Dedicated compartments protect electrical and hydraulic components

Emergency Shut-Off at Platform and Lower Controls

Non-Skid Steel Deck Construction

Motion Alarm

Drive Speed Interlock

Multi-Axis Tilt Sensor

Multiple Disc Brakes, manual brake release

Scissor Maintenance Lock

Dual Automatic Parking Brake

Other Features

Fold-Down Guardrails

Hour Meter

Powder Coat Finish

Lifting Lugs

Machine Tie Downs

Optional Features

Lanyard Attachments (6)	120V 2250W Generator
Flashing Beacon (continuous)	Foam-Filled (standard) Tires
Automotive Horn	Non-Marking RT Tires (air-filled)
Removable Upper Controls	Non-Marking RT Tires (foam-filled)
Platform Swing Gate (standard on CE and CSA)	High Flotation Tires (air-filled)
Air Line to Platform	High Flotation Tires (foam-filled)
All Motion Alarm	Additional LPG Tank
Quad-Trax™ 4wd	Diesel Engine
Auto-Leveling Outriggers	Australian Compliant Options
Platform Work Lights	CSA Compliant Options
	1 or 2 Year Extended Warranty



MEC Aerial Work Platforms

1775 Park Street, #77 | Selma, CA 93662 | USA

Toll free: 1.877.MEC LIFT | 1.877.632.5438

Tel: 559.891.2488 | Fax: 559.891.2448

Email: info@mecAWP.com

www.mecAWP.com

91 SERIES RT 1108

Model	2591RT		3391RT		4191RT	
	U.S.	Metric	U.S.	Metric	U.S.	Metric
Heights						
Working Height*	31 ft.*	9.62 m*	39 ft.*	12.06 m*	47 ft.*	14.50 m*
Platform Height	25 ft.	7.62 m	33 ft.	10.06 m	41 ft.	12.50 m
Maximum Drive Height	25 ft.	7.62 m	33 ft.	10.06 m	41 ft.	12.50 m
Stowed Height (Top Guardrail)	100 ½ in.	2.55 m	109 ½ in.	2.78 m	119 ft.	3.00 m
Stowed Height (Rails Folded)	71 in.	1.80 m	79 in.	2.00 m	87 ½ in.	2.22 m
Platform Entry Height	57 in.	1.45 m	66 in.	1.67 m	74 in.	1.88 m
Guardrail Height	44 ½ in.	1.13 m	44 ½ in.	1.13 m	44 ½ in.	1.13 m
Toeboard Height	7.0 in.	18 cm	7.0 in.	18 cm	7.0 in.	18 cm
Ground Clearance	12.0 in.	30.48 cm	12.0 in.	30.48 cm	12.0 in.	30.48 cm
Dimensions						
Overall Length (Stowed)	144 in.	3.66 m	144 in.	3.66 m	144 in.	3.66m
Overall Length (With Outriggers)	180 in.	4.57 m	180 in.	4.57 m	180 in.	4.57 m
Width	91 in.	2.31 m	91 in.	2.31 m	91 in.	2.31 m
Platform Length (Extended)	180 in.	4.57 m	180 in.	4.57 m	180 in.	4.57 m
Platform Length (Retracted)	132 in.	3.35 m	132 in.	3.35 m	132 in.	3.35m
Roll-Out Deck Length	48 in.	1.22 m	48 in.	1.22 m	48 in.	1.22 m
Wheelbase	102 ½ in.	2.60 m	102 ½ in.	2.60 m	102 ½ in.	2.60 m
Lift Capacity	2,000 lbs	907 kg	1,500 lbs	680 kg	1,000 lbs	454 kg
Roll-Out Deck Capacity	500 lbs	227 kg	500 lbs	227 kg	500 lbs	227 kg
Speeds						
Raise/Lower Speed	25/30 sec.		33/35 sec.		34/40 sec.	
Drive Speed (Stowed)	3.8 mph	6.1 km/h	3.8 mph	6.1 km/h	3.8 mph	6.1 km/h
Drive Speed (Raised)	0.8 mph	1.3 km/h	0.8 mph	1/3 km/h	0.8 mph	1.3 km/h
Performance						
Gradeability	45%/26°		45%/26°		45%/26°	
Turning Radius (Inside)	76 in.	1.93 m	76 in.	1.93 m	76 in.	1.93 m
Turning Radius (Outside)	195 in.	4.95 m	195 in.	4.95 m	195 in.	4.95m
Weight (Approximately**)	8,000 lbs**	3629 kg**	8,700 lbs**	3946 kg**	9,700 lbs**	4400 kg**
Brakes	Multi-disc					
Power Source	Liquid-cooled, Kubota DF752 Dual Fuel or Kubota D1105 Diesel engine					
Controls	Proportional drive and lift controls					
Drive	Planetary drive/two-speed wheel motors					
Hydraulics	Variable displacement					
Axle Oscillation	Rear axle					
Tires	12-16.5 NHS "Outrigger"					
Fuel Tank Capacity	15 gallons (57 liters)					
Hydraulic Fluid Capacity	23 gallons (87 liters)					

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.

**Weight may vary with certain options or configurations. When platform is elevated, all models must be on a firm, level surface.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only.

Meets or exceeds the requirements of ANSI A92.6-2006, CSA B354.2-01, AS 1418.10 and CE Compliance as applicable. Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by:

